

EFP BATTERY PACK CROSS REFERENCE LIST

LPS ITEM #	DIMENSIONS	IOTA ITEM #	Remarks	BODINE ITEM #	Remarks	Compatible lamps with LPS model
EFP 42GS	9.4"L x 2.4"W x 1.5"H	I-42-EM-A	IOTA model includes AC-output and time-delay features; ALP model has single LED switch	B94CG	BODINE model includes time-delay feature; ALP model includes a single LED switch	(1) 13W-42W or (2) 13W-39W (4-pin) CFL; (1) 17W-40W T8, T10 and T12 fluorescent lamps
EFP 32GS	9.4"L x 2.4"W x 1.5"H	I-32	IOTA model includes time-delay feature and is of low-profile	B100	BODINE model includes time delay feature; ALP model includes a single LED switch	(1) 17W-40W T8, T10, T12 fluorescent lamp including linear, U-shaped, Circline and (4-pin) CFL
EFP 48GS	9.4"L x 2.4"W x 1.5"H	I-48	IOTA model includes time-delay feature	B60	BODINE model includes time-delay feature; ALP model includes a single LED switch	(1) 13W-42W or (2) 13W-39W (4-pin) CFL; (1) 17W-110W or (2) 17W-40W T8, T10, T12 fluorescent lamps including linear, U-shaped and Circline
EFP 80GS	13.3"L x 2.4"W x 1.5"H	I-320	IOTA model includes time-delay feature and is of low-profile	B50	BODINE model includes time-delay feature; ALP model includes a single LED switch	(1) 13W-42W or (2) 13W-39W (4-pin) or (1) 17W-55W long (4-pin) CFL; (1) 17W-215W or (2) 17W-40W T8, T10, T12 fluorescent lamps including linear, U-shaped and Circline
EFP 160GS	16.3"L x 5.5"W x 1.75"H	I-160	IOTA model has different dimensions	B30	BODINE model includes a time-delay feature	(2) 13W-42W (4-pin) or (1) 17W-55W long (4-pin) CFL; (1) 17W-215W or (2) 17W-40W T8, T10, T12 fluorescent lamps including linear, U-shaped and Circline
Low-Profile ACTD						
EFP SL28GS	4.3"L x 1.25"W x 1.25"H	ISL-28	ALP model includes AC-output feature	LP400 or LP500	LP400 is 0.4" wider than ALP model with a separate switch and LED indicator; LP500 is 4.1" longer than ALP model and can be used in sealed and gasketed fixtures; BEST model has AC-output feature	(2) 13W (4-pin) CFL; (1) 8W-28W T5 or (1) 17W-32W T8, T10, T12 fluorescent lamps including linear, U-shaped and Circline
EFP SL32GS	10.0"L x 2.0"W x 1.2"H	SL-32	ALP model is 0.5" longer and includes the AC output feature	B100LP	BODINE model is almost 7" longer and little thinner, can be used with sealed and gasketed fixtures; ALP model includes AC-output feature	(1) 13W-26W (4-pin) CFL; (1) 14W-28W T5 or (1) 17W-40W T8, T10, T12 fluorescent lamps including linear, U-shaped and Circline
EFP SL48GS	13.3"L x 2.25"W x 1.3"H	N/A	None	B60LP	BODINE model is 3" longer and little thinner, can be used with sealed and gasketed fixtures; ALP model includes AC-output feature	(1) 13W-42W (4-pin) or (1) 17W-55W long (4-pin) CFL; (1) 14W-54W T5HO or (1) 17W-40W T8, T10, T12 fluorescent lamps including linear, U-shaped and Circline
EFP SL54GS	7.75"L x 1.25"W x 1.25"H	ISL-54	ALP model includes AC-output feature	LP550	BODINE model is 1" longer and can be used in sealed and gasketed fixtures; ALP model has AC-output feature	(1) 13W-50W (4-pin) or long (4-pin) CFL; (1) 8W-28W T5 or (1) 17W-40W T8, T10, T12 fluorescent lamps including linear, U-shaped and Circline
EFP SL540GS	21.5"L x 1.22"W x 1.15"H	ISL-540	ALP model includes AC-output feature	LP600	BODINE model can be used in sealed and gasketed fixtures; BEST model has AC-output feature	(1) 13W-26W or (2) 13W-18W (4-pin) or long (4-pin) CFL; (1) 8W-54W or (2) 8W-14W T5; T5HO or (1) 17W-40W T8, T10, T12 fluorescent lamps including linear, U-shaped and Circline
EFP SL80GS	14.25"L x 2.0"W x 1.2"H	I-320	ALP model includes AC-output feature, is 1.25" longer, and little thinner in comparison to IOTA's model	B50LP	BODINE model is almost 7" longer and little thinner, can be used with sealed and gasketed fixtures; ALP model includes AC-output feature	(1) 13W-42W or (2) 13W-39W (4-pin) or (1) 17W-55W long (4-pin) CFL; (1) 14W-54W T5HO or (2) 17W-40W T8, T10, T12 fluorescent lamps including linear, U-shaped and Circline