

LED-9150 150W High Bay HID Luminaire



Models

LED-9150-50K, 120-277 VAC, cULus, 5000K

Features


- 150 Watts Replaces 400w HID Luminaire equivalent
- 120° Beam Angle
- 120-277V UL 1993
- UL classified for damp environments (USA & Can)
- >50,000 rated LED life
- 5 year limited warranty (see website for details)
- 5000K CCT
- Includes 3' three-wire corded whip



Technical Specifications

Models US/CAN	LED-9150-50K
CCT	5000K
Power Consumption	150 Watts
Replaces	400 MH/HPS
Mounting	n/a
Voltage	120-277VAC
LED Type	2835
Beam Angle	120°
Dimmable	No
Operating Temp	-40°F - +122°F
Rated R70 Life	Up to 50,000 Hrs.
Warranty	5 Year Limited*
LM79 Specifications	
Power (W)	161.2
CCT	3603
Light Output	18712
Efficacy	116
THD @ 277V	16.61%
PF @ 277V	0.98
CRI:	81.2
R9	2
Duv	0.0022
Packaging	
Unit	Master/ 2
Master	26.6" x 26.6" x 6.5"
	27.55" x 27.55" x 13.58"

Lux Distance Curve



LED-9150-50K

LED Power Consumption (Watts)	HID Power Consumption (Watts)	HID Ballast Power Consumption (Watts)	Total Savings (Watts)	Annual Energy Savings (14 hrs/day)	Lifetime Energy Savings (over 50,000 hrs)
150	400	60	310	\$174	\$1,705.00

	MODEL	DLC CODE
	LED-9150-50K	PF9QN4HF
Approved Categories:		
High-Bay Luminaires for Commercial and Industrial Buildings		



188 S. Northwest Highway • Cary, IL 60013
 (847) 380-3540 • FAX: (847) 380-3542
www.led-llc.com

